

DECLARATION OF PERFORMANCE

In accordance with Regulation (EU) 305/2011 on construction products and Regulation (EU) 574/2014 on its amendment

Rigips® Habito® Hydro 15
DoP_Habito Hydro_15_004

1. Unique identification code of the product-type:

Rigips® Habito® Hydro PRO (DFRIH1) 15

Controlled density fire resistant impregnated board with enhanced strength and improved surface hardness

2. Intended use/es:

Building material for partition walls and suspended ceilings

Area code: 7 - Gypsum products

3. Manufacturer:

Saint-Gobain Hungary Kft.
H-2085 Pilisvörösvár, Bécsi út 07/5 hrsz.
www.rigips.hu

4. Authorised representative:

-

5. System/s of AVCP:

System 4.

6.a Harmonised standard:

MSZ EN 520:2004+A1:2009

7. Declared performance/s:

Essential characteristics	Performance	Harmonised technical specification
Product type	DFRIH1	MSZ EN 520:2004+A1:2009
Reaction to fire	A2-s1, d0	
Nominal thickness	15 mm	
Thermal conductivity	0,25 W/m*K	
Density	>940 kg/m ³	
Water vapour diffusion resistance factor μ	6-10	
Longitudinal flexural strength F	min. 1000 N	
Transverse flexural strength F	min. 500 N	
Water absorption class	H1	
Total water absorption	<5 %	
VOC	A+	
Dangerous substance	NPD	
*Impact resistance	NPD	
*Fire resistance	NPD	
*Airborne sound insulation	NPD	

*These features are system dependent and can be found in the manufacturers documentation at www.rigips.hu.
NPD= No Performance Determined

8. The performance of the product identified in point 1. is in conformity with the declared performance in point 7.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Máté-Toth Nándor
Rigips Gyárvezető

Pilisvörösvár, 2025-02-01